

Surtur Series

USER MANUAL

Thermal Imaging Monocular



S1-635L

CONTENTS

1. Product Overview	01
2. Product Components	02
3. Package Contents	03
4. Operation Instructions	03
5. Button Functions	05
6. Menu Functions	06
7. Device Connection	08
8. Specifications	09
9. Maintenance and Care	11



1. Product Overview

1. S1-635L is an infrared thermal imaging telescope designed for observation and ranging under low-light or adverse weather conditions.

2. The device detects thermal radiation from target objects. The thermal imaging module captures the image signal, processes it, and transmits it to an OLED display. Users can then view a magnified, clear image through the eyepiece. Additionally, real-time image observation, monitoring, and system adjustments can be performed via a smartphone app.

3. High-resolution thermal imaging module paired with a large-aperture infrared lens, delivering high-quality thermal images.

Adjustable eyepiece focus, allowing clarity optimization for targets ranging from 5 meters to infinity.

2. Product Components



1. Device Indicator	2. Objective Lens Focus Ring	3. Objective Lens
4. Rangefinder Module	5. Power Button	6. Menu Button
7. Eyepiece Focus Cover	8. Eyepiece Lens	9. Data Port Cover
10. Lens Cap	11. Up Navigation Button	12. Down Navigation Button
13. Battery Compartment Cover		

3. Package Contents

- ▶ S1-635L Thermal Imaging Monocular
- ▶ 18650 Battery
- ▶ Anti-Slip Wrist Strap
- ▶ Type-C Data Cable
- ▶ 5V/2A Adapter
- ▶ User Manual

4. Operation Instructions

4.1. Warnings

- (1) Do not point the thermal imaging camera directly at the sun, CO₂ lasers, welding machines, or other high-intensity radiation sources.
- (2) The interval between two power cycles should be at least 20 seconds.
- (3) Handle with care during operation. Avoid dropping, striking, or subjecting the device to vibrations, as this may damage optical/electronic components or cause structural deformation.
- (4) Do not disassemble the thermal imaging camera. In case of malfunction, contact the manufacturer immediately. Unauthorized disassembly will void the warranty.
- (5) When not in use or during transportation, remove the battery and store the thermal imaging camera in a protective carrying case.
- (6) Replace the battery promptly when the battery level is low to prevent deep discharge, which may damage the battery.
- (7) Using the device outside the specified operating conditions may cause damage to the thermal imaging camera.

4.2. Usage Method

- (1) Unpack the thermal imager, install the battery, then press and hold the power button for 3 seconds to turn it on.
- (2) Look through the eyepiece at the internal display, and manually adjust the diopter ring until the symbols and numbers on the screen appear sharp and clear.
- (3) Aim the thermal imaging lens at the target object, then fine-tune the diopter ring of the imaging module until the observed object is in clear focus.

4.3. Precautions

- (1) Clean the product's optical components (thermal imaging objective lens, eyepiece, and laser rangefinder lens) only when dirt affects image quality.
Method: Gently wipe the soiled area of the lens surface with a lens cloth lightly moistened with alcohol. Avoid excessive rubbing to prevent damage to the anti-reflective coating.
- (2) Turn off the device immediately after use or if no observation is performed for an extended period after startup. This helps prolong the effective service life of the thermal imaging telescope.

5. Button Functions



Power Button

- (1) Press and hold for 3 seconds to power on/off.
- (2) Press and hold for 1-3 seconds to enter sleep mode. Short-press to wake from Sleep mode.
- (3) Short-press to refresh in observation mode.

Up Navigation Button

- (1) Press briefly to navigate up or switch display modes.
- (2) Press and hold for 1.5-3 seconds to take a photo; hold for over 3 seconds to start/stop video recording.

Menu Button

- (1) Press briefly to access the menu. Use the navigation buttons to move through options.
- (2) Press and hold to return to the previous menu level in menu mode.

Down Navigation Button

- (1) Press briefly to navigate down or switch magnification (1x, 2x, 4x, 8x).
- (2) Press and hold to enable/disable the rangefinder.

6. Menu Functions

Icon	Main Menu	Function Description
	Mode Selection	<p>Mode options include 5 items: "White Hot, High Light, Black Hot, Low Light, Pseudo-color". Default mode is White Hot.</p>      <p>White Hot High Light Black Hot Low Light Pseudo-color</p>
	WiFi	<ol style="list-style-type: none"> Turn on the Wi-Fi in the device menu, then enable Wi-Fi on your phone and open the testing software APP. Locate the MAC address named "APPshow-XX-XXXXX" in your phone's Wi-Fi list, enter password "12345678" to connect the device. After connecting the device to the phone via Wi-Fi, real-time captured images can be viewed.
	Ranging Unit Selection	Two options available: Meters / Yards
	Screen Brightness	Press the menu button to enter brightness settings with 10 options. Selecting any option causes corresponding changes in the screen display. Choose the appropriate level based on usage preference.
	Brightness	Press the menu button to enter contrast settings with 10 options. Selecting any option causes corresponding changes in imaging brightness.
	Contrast	Press the menu button to enter contrast settings with 10 options. Selecting any option causes corresponding changes in the imaging display. Higher values result in stronger image contrast.
	Image Detail Boost	Press the menu button to enter image detail enhancement options. Higher values reveal more details.
	Advanced Settings	<ul style="list-style-type: none"> ▶ Video Output Enable/disable CVBS video output function. ▶ Date/Time Select "Date/Time" menu, short-press menu button to enter sub-options. Short-press menu button to move between options, short-press Up/Down keys to adjust values. Long-press menu button to save and exit after adjustment. ▶ Multi-language Press the menu button to enter the language settings. Use the Up/Down keys to select the desired language, then short-press the menu button to confirm.

	<p>Advanced Settings</p>	<ul style="list-style-type: none"> ▶ Recording Audio Move cursor to "Recording Audio" and press menu button to open sub-menu. Select "On" or "Off" to enable/disable audio recording during video capture. ▶ Format Enter format sub-menu, short-press menu button to select "Confirm" or "Cancel". Operate with caution! Data cannot be recovered after deletion! ▶ Auto Shutdown Options: 3 minutes, 5 minutes, Off (Default). After powering on, users can select either 3 or 5 minutes for automatic shutdown. ▶ Default Settings Move cursor to "Default Settings" and press menu button to open sub-menu. Select "Confirm" or "Cancel" to restore factory default settings. Operation will reset device to factory default state. Proceed with caution. ▶ Dead Pixel Repair Move cursor to "Dead Pixel Repair" menu, short-press menu button to enter sub-menu. Toggle between "Auto Repair" and "Manual Repair" modes using Up/Down keys. Cover the lens cap before repair and follow prompts. (1) Select "Auto Repair", short-press menu button to complete repair. (2) Select "Manual Repair", move cursor with Up/Down keys, toggle options with Power button, short-press menu button to save. ▶ Image Calibration Enter Image Calibration menu. To calibrate, select "Confirm", cover the lens cap, then short-press menu button to calibrate background image uniformity. Calibration results save automatically upon completion. ▶ Version Information Move cursor to "Version" and press menu button to view device software version information.
---	--------------------------	---

7. Device Connection


Download the dedicated app to connect the device to your mobile device via WiFi.



Android/iOS: Scan to download




Search "XVision" on Google Play to Download.



Download and install the app



Turn on the device and enable WiFi.I



Select WiFi "xx." and connect
(Default WiFi password: [12345678](#))



Open the App

8. Specifications



46.5mm



82.9mm

168.5mm/176mm

S1-635L

Sensor	
Type	Uncooled Vanadium Oxide (VOx)
Resolution	640x512
Frame Rate	50 Hz
Pixel Size	12μm
NETD	≤18mk
Optics	
Objective Lens	25/35mm/F1.0
Base Magnification	1.4X/2X
Digital Zoom	1x / 2 x/ 4 x/ 8x
Eye Relief	30mm
Diopter Adjustment	+5/-5 D
Focus Distance	5m - ∞
Field of View	17.5°X13.1°/12.5°X9.4°
Detection Range (Target Size: 1.7m x 0.5m)	1250m/1750m

Display	
Operating Modes	White Hot, High Light, Black Hot, Low Light, Pseudo-color
Type/Resolution	0.39 inch / OLED / 1024X768
Power	
Voltage	3-4.2 V
Battery	18650 Li-ion, 3500mAh
External Power	5V (USB)
Runtime	5 hours
Waterproof Rating	IP67
Operating Temperature	-20°C~+50°C
Dimensions	168.5x46.5x82.9mm/176x46.5x82.9mm
Weight	394g/402g
Recording	
Video/Photo Resolution	1024x768
Video/Photo Format	.mp4 / .jpg
Storage	Built-in 32GB memory card
Wireless	
Frequency	2.4GHz
Standard	802.11 b/g
WiFi Range	15m
Rangefinder	
Wavelength	905nm
Maximum Range	1000m
Accuracy	+ /-1m

9. Maintenance and Care

- (1) The lens of thermal imaging camera is a critical optical component. During installation and use, avoid contact with oil, chemicals, or other contaminants that may damage the lens surface. Always cover the lens with the lens cap after use.
- (2) When not in use or during transportation, remove the battery and store the thermal imaging camera in its protective case.
- (3) For long-term storage or periods of inactivity, keep the thermal imaging camera in a cool, dry environment.
- (4) Do not clean the housing of the thermal imaging camera with chemical solvents or thinners. Instead, use a clean, soft, and dry lint-free cloth.
- (5) If the device is not used for an extended period, power it on and perform a calibration check at least once every six months.

FCC Caution:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.

-Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

-Consult the dealer or an experienced radio/TV technician for help.

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.



Thermal Imaging & Night Vision

www.falconoptic.com